

制御用ポリエチレン絶縁ノンハロゲンシースケーブル (遮へい付)・・・EM-C E E-S

公称 断面積 mm ²	線心数	導体		絶縁体 厚さ mm	シース 厚さ mm	仕上 外径 約mm	最大導 体抵抗 (20°C) Ω/km	試験 電圧 V・1分	最小絶 縁抵抗 (20°C) MΩ・km	概算 重量 kg/km
		構成 素線数/素線径	外径 mm							
1.25	2	7/0.45	1.35	0.8	1.5	9.6	16.8	2000	2500	115
	3				1.5	10.5				135
	4				1.5	11.0				150
	5				1.5	12.0				175
	6				1.5	13.0				205
	7				1.5	13.0				215
	8				1.5	13.5				240
	10				1.5	15.5				295
	12				1.5	16.0				325
	15				1.5	17.0				385
	20				1.5	19.0				475
	30				1.6	23.0				680
	2.0				2	7/0.6				1.8
3		1.5	11.5	170						
4		1.5	12.0	200						
5		1.5	13.0	235						
6		1.5	14.0	275						
7		1.5	14.0	290						
8		1.5	15.0	330						
10		1.5	17.5	400						
12		1.5	18.0	455						
15		1.5	19.5	540						
20		1.6	22.0	685						
30		1.7	26.0	990						
3.5		2	7/0.8	2.4	0.8		1.5	12.0	5.30	
	3	1.5				12.5	235			
	4	1.5				13.5	275			
	5	1.5				14.5	330			
	6	1.5				16.0	390			
	7	1.5				16.0	415			
	8	1.5				17.0	475			
	10	1.5				20.0	585			
	12	1.5				21.0	670			
	15	1.6				22.0	815			
	20	1.7				25.0	1050			
	30	1.9				30.0	1540			
	5.5	2				7/1.0	3.0	1.0		1.5
3		1.5	14.5	325						
4		1.5	16.0	400						
5		1.5	17.5	480						
6		1.5	19.0	565						
7		1.5	19.0	610						
8		1.5	21.0	695						
10		1.6	24.0	855						
12		1.7	25.0	995						
15		1.8	27.0	1220						
20		1.9	31.0	1570						