

制御用ポリエチレン絶縁ノンハロゲンシースケーブル (遮へい付)・・・EM-C E E-S

| 公称 断面積 mm ² | 線心数 | 導体 | | 絶縁体 厚さ mm | シース 厚さ mm | 仕上 外径 約mm | 最大導 体抵抗 (20°C) Ω/km | 試験 電圧 V・1分 | 最小絶 縁抵抗 (20°C) MΩ・km | 概算 重量 kg/km |
|------------------------------|-----|---------------|----------|-----------------|-----------------|-----------------|------------------------------|------------------|-------------------------------|-------------------|
| | | 構成 素線数/素線径 | 外径 mm | | | | | | | |
| 1.25 | 2 | 7/0.45 | 1.35 | 0.8 | 1.5 | 9.6 | 16.8 | 2000 | 2500 | 115 |
| | 3 | | | | 1.5 | 10.5 | | | | 135 |
| | 4 | | | | 1.5 | 11.0 | | | | 150 |
| | 5 | | | | 1.5 | 12.0 | | | | 175 |
| | 6 | | | | 1.5 | 13.0 | | | | 205 |
| | 7 | | | | 1.5 | 13.0 | | | | 215 |
| | 8 | | | | 1.5 | 13.5 | | | | 240 |
| | 10 | | | | 1.5 | 15.5 | | | | 295 |
| | 12 | | | | 1.5 | 16.0 | | | | 325 |
| | 15 | | | | 1.5 | 17.0 | | | | 385 |
| | 20 | | | | 1.5 | 19.0 | | | | 475 |
| | 30 | | | | 1.6 | 23.0 | | | | 680 |
| | 2.0 | | | | 2 | 7/0.6 | | | | 1.8 |
| 3 | | 1.5 | 11.5 | 170 | | | | | | |
| 4 | | 1.5 | 12.0 | 200 | | | | | | |
| 5 | | 1.5 | 13.0 | 235 | | | | | | |
| 6 | | 1.5 | 14.0 | 275 | | | | | | |
| 7 | | 1.5 | 14.0 | 290 | | | | | | |
| 8 | | 1.5 | 15.0 | 330 | | | | | | |
| 10 | | 1.5 | 17.5 | 400 | | | | | | |
| 12 | | 1.5 | 18.0 | 455 | | | | | | |
| 15 | | 1.5 | 19.5 | 540 | | | | | | |
| 20 | | 1.6 | 22.0 | 685 | | | | | | |
| 30 | | 1.7 | 26.0 | 990 | | | | | | |
| 3.5 | | 2 | 7/0.8 | 2.4 | 0.8 | | 1.5 | 12.0 | 5.30 | |
| | 3 | 1.5 | | | | 12.5 | 235 | | | |
| | 4 | 1.5 | | | | 13.5 | 275 | | | |
| | 5 | 1.5 | | | | 14.5 | 330 | | | |
| | 6 | 1.5 | | | | 16.0 | 390 | | | |
| | 7 | 1.5 | | | | 16.0 | 415 | | | |
| | 8 | 1.5 | | | | 17.0 | 475 | | | |
| | 10 | 1.5 | | | | 20.0 | 585 | | | |
| | 12 | 1.5 | | | | 21.0 | 670 | | | |
| | 15 | 1.6 | | | | 22.0 | 815 | | | |
| | 20 | 1.7 | | | | 25.0 | 1050 | | | |
| | 30 | 1.9 | | | | 30.0 | 1540 | | | |
| | 5.5 | 2 | | | | 7/1.0 | 3.0 | 1.0 | | 1.5 |
| 3 | | 1.5 | 14.5 | 325 | | | | | | |
| 4 | | 1.5 | 16.0 | 400 | | | | | | |
| 5 | | 1.5 | 17.5 | 480 | | | | | | |
| 6 | | 1.5 | 19.0 | 565 | | | | | | |
| 7 | | 1.5 | 19.0 | 610 | | | | | | |
| 8 | | 1.5 | 21.0 | 695 | | | | | | |
| 10 | | 1.6 | 24.0 | 855 | | | | | | |
| 12 | | 1.7 | 25.0 | 995 | | | | | | |
| 15 | | 1.8 | 27.0 | 1220 | | | | | | |
| 20 | | 1.9 | 31.0 | 1570 | | | | | | |