

ビニルキャブタイヤケーブル (VCT)

公称 断面積 mm ²	線心数	導体		絶縁体 厚さ mm	シース 厚さ mm	仕上 外径 約mm	導体抵抗		試験 電圧 V・1分	絶縁 抵抗 (20°C) MΩ・km	概算 重量 kg/km	標準 条長 m
		構成 素線数/素線径	外径 mm				A (20°C) Ω/km	TA (20°C) Ω/km				
0.75	2	30/0.18	1.1	0.8	1.7	8.8	25.1	26.6	3000	50	100	200
	3										110	
	4										135	
1.25	2	50/0.18	1.5	0.8	1.7	9.6	15.1	16.0	3000	50	120	200
	3										140	
	4										175	
2.0	2	37/0.26	1.8	0.8	1.8	10.5	9.79	10.2	3000	50	150	200
	3										175	
	4										210	
3.5	2	45/0.32	2.5	0.8	1.8	12.0	5.24	5.54	3000	40	205	200
	3										255	
	4										320	
5.5	2	70/0.32	3.1	1.0	2.0	14.5	3.37	3.56	3000	40	305	200
	3										370	
	4										460	
8.0	2	50/0.45	3.7	1.2	2.1	16.5	2.39	2.52	3000	40	410	200
	3										510	
	4										640	

