

しゃへいビニルキャブタイヤケーブル (VCTS)

公称 断面積 mm <sup>2</sup>	線心数	導体		絶縁体 厚さ mm	しゃへい 厚さ mm	シース 厚さ mm	仕上 外径 約mm	導体抵抗		試験 電圧 V・1分	絶縁 抵抗 (20℃) MΩ・km	標準 条長 m
		構成 素線数/素線径	外径 mm					A (20℃) Ω/km	T A (20℃) Ω/km			
0.75	2	30/0.18	1.1	0.8	0.3	1.7	9.7	25.1	26.6	3000	50	200
	3											
	4											
1.25	2	50/0.18	1.5	0.8	0.3	1.8	10.5	15.1	16.0	3000	50	200
	3											
	4											
2.0	2	37/0.26	1.8	0.8	0.3	1.8	11.1	9.79	10.2	3000	50	200
	3											
	4											
3.5	2	45/0.32	2.5	0.8	0.35	1.9	12.8	5.24	5.54	3000	40	200
	3											
	4											
5.5	2	70/0.32	3.1	1.0	0.35	2.0	15.2	3.37	3.56	3000	40	200
	3											
	4											
8.0	2	50/0.45	3.7	1.2	0.35	2.2	17.6	2.39	2.52	3000	40	200
	3											
	4											

